

 **DUNLOP**



RUNSCOOT *D307*

RUNSCOOT *D307*

Neumático perfecto para diferentes tipos de scooters, permite una conducción suave y estable.



NEUMÁTICOS

D307/ D307F

D307A



MEDIDAS

D307 <Común para neumáticos delanteros y traseros>

Tamaño	Tipo	Código	Ancho de arrio estándar (pulg)	Ancho de arrio permitido (pulg)	Ancho (mm)	Diámetro total (mm)
8"	3.00-8 26J	WT 305525	2.15	1.85-2.50	83	360
10"	2.50-10 33J	WT 305501	1.50	1.50	65	388
	2.75-10 38J	WT 305503	1.50	1.50-1.85	71	394
	3.00-10 42J	WT 305505	2.15	1.85-2.50	81	413
	3.00-10 42J	TL 305507	2.15	1.85-2.50	82	414
	3.50-10 51J	TL 305509	2.50	2.15-2.50	97	441
	80/100-10 46J	TL 305519	1.85	1.85-2.15	81	414
	80/90-10 44J	TL 305511	2.15	1.85-2.15	81	398
	90/100-10 53J	TL 305515	2.15	1.85-2.50	93	441
	90/90-10 50J	TL 305513	2.15	2.15-2.50	93	420
	100/90-10 56J	TL 305517	2.50	2.15-2.75	101	434
12"	90/90-12 44J	TL 305521	2.15	1.85-2.50	89	467
	100/80-12 56J	TL 305523	2.50	1.85-2.75	96	462

D307F <Delantero>

Tamaño	Tipo	Código	Ancho de arrio estándar (pulg)	Ancho de arrio permitido (pulg)	Ancho (mm)	Diámetro total (mm)
14"	80/90-14M/C 40P	TL 314049	1.85	1.85-2.15	76	500
	90/90-14M/C 46P	TL 314053	2.15	1.85-2.50	89	519
16"	80/90-16M/C 43P	TL 314057	1.85	1.60-2.15	78	549

D307A <Trasero>

Tamaño	Tipo	Código	Ancho de arrio estándar (pulg)	Ancho de arrio permitido (pulg)	Ancho (mm)	Diámetro total (mm)
10"	110/80-10 58J	TL 323638	2.50	2.15-3.00	107	425
14"	90/90-14M/C 46P	TL 314051	2.15	1.85-2.50	88	518
	100/90-14M/C 51P	TL 314055	2.50	1.85-2.75	101	535

